

HARDWARE FEATURES

- Automated turntable to fixture parts to ensure held in place during operation
- Clean In Place (CIP) system - when finishing is complete, nozzles rinse parts in the same chamber
- Hinged electrical panel design allows for easy access for maintaining controls and motor
- Fully welded stainless steel chamber provides corrosion resistance and operator safety
- Pumping system with easy maintenance
- Casters for easy installation / relocation

RESULTING IN...

- + Preserving fine feature part detail
- + Fast cycle times
- + Automated finishing

SOFTWARE FEATURES

- Patent-pending AUTOMAT3D™ platform
- Proprietary Agitation Algorithms
- Variable temperature up to 130°F (54°C)
- Intelligent cycle times
- Customizable settings
- One-touch repeatability with recipes storage
- Media Separation Sequence
- Pre-programmed preventative maintenance schedules

RESULTING IN...

- + Minimal operator intervention
- + Precision machine programming
- + Consistency and repeatability



PRODUCT SPECIFICATIONS

SIZE & WEIGHT SPECIFICATIONS

- **Envelope:**
Both Nozzles: 15" L x 15" W x 12" H
(38 cm x 38 cm x 30.4 cm)
Top Nozzle Only: 15" L x 15" W x 15" H
(38 cm x 38 cm x 38 cm)
- **Machine Footprint (Chamber Door Closed):**
69.5" L x 37" W x 94" H
(177 cm x 94 cm x 239 cm)
Machine Footprint (Chamber Door Open):
69.5" L x 67" W x 94" H
(177 cm x 170 cm x 239 cm)
- **Approx. Weight:** 2180 lbs. (989 kg) empty;
2350 lbs. (1066 kg) full

ELECTRICAL SPECIFICATIONS

- Voltage: 480V 3 Phase
- Amperage: 25A
- Connector: HBLS430C7W
- **other voltage options available

CONSUMABLES

- PLM-001-DUO detergent
- ZB-CBM, MB-CBM, ZS-CBM425, AS-ALO and PS-SS suspended solids

SAFETY FEATURES

- Emergency stop
- External LED lighted chamber
- Sealed chamber with door safety lock
- Compliant with all OSHA regulations
- CE

MATERIALS AND TECHNOLOGIES



DMLS •
SLM • DED

Authorized Distributor:



POSTPROCESS TECHNOLOGIES INC.

2495 Main Street, Suite 615, Buffalo NY 14214 USA
info@postprocess.com +1.866.430.5354