

# XFlow 2019x DATA SHEET

## ENGINE

### Solver

- Fully Lagrangian kinetic solver—Lattice Boltzmann Method
- Compressible / Enforced incompressible (Labs mode)
- Transient
- 2D / 3D
- Single Phase flow: internal / external (Virtual Wind Tunnel)
- Free surface flow: internal / external (Water channel)
- Multiphase flow with two immiscible fluids: Particle-based tracking / Phase field / VoF
- Discrete Phase Model (DPM)
- Heat transfer: conduction / convection / energy-momentum coupling
- Buoyancy: Boussinesq approximation
- Radiation: surface-to-surface Montecarlo model
- Supersonic flow model (Labs mode)
- XFlow One engine: improved performance for single phase flow
- Turbulence flow: Large Eddy Simulation (LES)
- Subgrid-scale turbulence model: Smagorinsky / dynamic Smagorinsky / Wall-Adapting Local-Eddy (WALE)
- Acoustics: Direct noise computation
- Non-Newtonian viscosity models: Herschel-Bulkley / Power-law / Cross / Carreau / user defined
- Fluid state equations: incompressible / ideal gas / Boussinesq model
- Scalar (species) transport equation - buoyancy effect

### Fluid-Structure Interaction (FSI)

- Multibody solver integrated and fully coupled with fluid solver
- Rigid body dynamics: up to 6 degrees of freedom / input mass properties / external forces and moments / automatic contact detection / friction and restitution coefficients
- Enforced: input position and angular laws
- Animated geometry: reading a geometry deformation sequence
- Two-way cosimulation between XFlow and Abaqus (Explicit/Implicit) for FSI analysis
- One-way cosimulation between XFlow and Abaqus (Explicit/Implicit) for FSI analysis with small deformation
- Two-way cosimulation between XFlow and Simpack via FMI standard
- Coupling with external CAE software supporting FMI standard such as OpenModelica
- Import of MSC Adams simulation results into XFlow

### Boundary Conditions

- Wall models: no-slip / free slip / turbulent boundary layer / universal wall model

- Immersed boundary method for moving walls treatment
- Inlet: velocity / mass flow / gauge pressure / gauge total pressure
- Progressive wave boundary condition for Water channel
- Outlet: gauge pressure / convective / velocity / velocity / mass flow / gauge total pressure
- Others: fan model / porous jump / porous volume (w/ or w/o heat generation) / periodicity
- Thermal analysis: adiabatic / temperature / temperature jump / heat flux / free convection / convection radiation / volume heat source / conjugate heat transfer / surface emissivity
- Absorbing inlet and outlet boundary conditions (LODI)

## USER INTERFACE

### General

- Unified working environment: pre-processing / domain generation / run / post-processing in a single Graphical User Interface (GUI)
- Configurable layout: dynamic windows and toolbars
- Advanced real-time graphics visualization
- Integrated ray-tracing and OpenGL post-processing
- Inputs: drop-down multiple-choice list / switch / user defined functions / tabular data
- XML project file format
- PowerBy approach to connect XFlow to the 3DEXPERIENCE® platform, import CAD models to XFlow and upload simulation results on the platform

### Pre-Processing

- Easy-to-use setup workflow
- Built-in modules for Virtual Wind Tunnel and Water-channel
- Geometry creation tools: basic-shapes generation / create mesh shape / duplicate shapes and faces
- Geometry modification tools: translation / rotation / scale / symmetry / split / heal / holes detection
- Geometry import: compatible standard formats: CATIA V5 / STEP / STL / IGES / BREP / NFF / NFB / CSFDB / OFF / BDF / Nastran Model
- Direct import of CATIA's CATPart and CATProduct geometries
- Automatic tessellation for parametric geometries
- Domain initialization from previous XFlow computations
- External mesh data import via VTK/VTU format as input laws
- Graphic function viewer for input laws
- User Defined Variables (UDV) inputs
- Symbolic function parser
- Define geometry behavior in an Arbitrary Reference Frame

# XFlow 2019x DATA SHEET

## Domain Generation

- Automatic domain generation (meshless technology) - octree-like grid
- Multi-resolution scheme, refinement criteria: near static walls / adaptive refinement / user defined region (rectangular, spherical, cylinder and tubular refinement regions) / curvature adapted
- Low geometry requirements ("watertight" only)
- Geometry motion and wake/free surface adaptive refinement: domain is dynamically and automatically refined (meshless technology)

## Run

- Start computation / Start advanced computation / Start FMU computation / Stop-Resume computation / Restart computation from a previous one
- FMU computation dialog box to perform co-simulations through FMI standard
- Batch mode available - command lines
- Serial multi-threaded computation (SMP)
- Distributed computation - MPI implementation supported: Intel, OpenMPI, MPICH2
- Job schedulers: LSF / SLURM / PBS-Torque / Custom
- Efficient scalability on shared and distributed memory environment

## Post-Processing

- Visualization mode: volumetric field / surface field distribution / markers / isocontours
- Visualization utilities: cutting planes / vectors / isosurfaces / stream tracers
- Function viewer for the monitoring of: stability parameter / forces / moments / probes data / mass-momentum integrals
- Post-process operations and measurement: probes and sensors (which can be associated to an arbitrary, even moving, geometry or reference frame), lines measurement, surface integral / volume integral / custom field calculation
- Post-processing tools for signal processing: Power Spectral Density (PSD) + filtering window functions
- Instantaneous, average, standard deviation and RMS data available
- Discrete Phase Model (DPM): spherical particles defined with their materials properties driven by the flow and external accelerations
- Export and import of post-processing setup for quicker analysis of simulation results
- Save XFlow simulation results on the **3DEXPERIENCE** platform for post-processing
- Export data to other formats: raw format / VTK / ParaView / EnSight Gold / CGNS / Surface data Abaqus / XFlow ASCII format / NASTRAN thermal data
- Generate animations from the simulations in video format or as images sequence
- Script and automation: numerical post-processing scripting possibilities (parsing numerical data binary file)

## Our 3DEXPERIENCE® platform powers our brand applications, serving 12 industries, and provides a rich portfolio of industry solution experiences.

Dassault Systèmes, the 3DEXPERIENCE® Company, provides business and people with virtual universes to imagine sustainable innovations. Its world-leading solutions transform the way products are designed, produced, and supported. Dassault Systèmes' collaborative solutions foster social innovation, expanding possibilities for the virtual world to improve the real world. The group brings value to over 210,000 customers of all sizes in all industries in more than 140 countries. For more information, visit [www.3ds.com](http://www.3ds.com).



3DEXPERIENCE®